



NC SANDING SEALER

NC SANDING SEALER is a general purpose sanding sealer for wood products. It is formulated with special materials to give outstanding flexibility, film strength and ease of sanding.

INTENDED USE : *For interior use on wooden products*

SPECIFICATIONS

Vehicle Type : *Nitrocellulose and Alkyd Resins.*

Solvents : *Hydrocarbons, ketones, alcohols and esters.*

Specific Gravity : *1.10 ± 0.10*

Solids (by weight) : *30 – 55%.*

Colour : *Clear*

Theoretical Spreading Rate : *8 – 10 sq. meter / litre @ 40 microns DFT*

APPLICATION

Finishing : *Low sheen.*

Drying Time : *Dry to touch* 5 – 10 minutes @ 25°C
Dry for sanding / overcoat 20 – 30 minutes @ 25°C
Dry for stacking 1 – 2 hour @ 25°C

Mixing Ratio : *Thin 100 parts of NC Sanding Sealer*
With 100 parts of NC Thinner or until desired viscosity is obtained.

Clean-up : *NC Thinner*

STORAGE AND CAUTIONS

Shelf Life : *1 year @ 25°C, provided that the product is stored under dry cool condition.*

Cautions : *Contents flammable.*
Keep away from heat, sparks and open flame.
Avoid contact with skin and eyes.
Avoid direct contact with vapour and spray mist.
Use with adequate ventilation.