



AC SEALER CLEAR

AC SEALER CLEAR is a two components Alkyd-Amino Clear high solids surfacer, which is specifically formulated to provide high film build with fast drying, hardness and good sanding properties.

INTENDED USE : *For interior use on wooden products*

SPECIFICATIONS

Vehicle Type : *Two components Alkyd-Amino. (Component A)*

Crosslinking Agent : *Acid Catalyst. (Component B)*

Viscosity : *±10.0 Poise @ 25°C*

Specific Gravity : *±1.13 g/cm³ @ 25°C*

Solid Content : *±65%*

Gloss at 60° : *NA*

Colour : *Clear.*

T S R (Dry 40 um)

Theoretical Spreading Rate : *8 – 10 sq. metres / litre (Catalyzed)*

APPLICATION

Diluent Solvent : *AC Thinner Mixed solvents of hydrocarbons, esters and alcohol.*

Drying Time : *Dust Free 5 – 10 minutes at room temperature*
Tack Free 10 – 15 minutes at room temperature

Mixing Ratio : *100 parts of 65 AC Sealer Clear*
10 parts of AC Hardener
40 parts of AC Thinner

Spray Viscosity : *14 – 16 sec NK2*

Pot Life : *> 8 hours*

STORAGE AND CAUTIONS

Shelf Life : *1 year @ 25°C, provided that the product is stored under dry cool condition.*

Cautions : *Contents flammable.*
Keep away from heat, sparks and open flame.
Avoid contact with skin and eyes.
Avoid direct contact with vapour and spray mist.
Use with adequate ventilation.-