



## **AC LACQUER TOPCOAT**

*AC LACQUER TOPCOAT is an acid-cured lacquer with excellent gloss and durability. It has a high solid content, good chemical resistance, coverage and abrasion resistance.*

---

**INTENDED USE** : *For interior use on wooden products*

### **SPECIFICATIONS**

**Vehicle Type** : *Alkyd and Amino Resins.*

**Solvents** : *Thinner, Hydrocarbons, ketones, alcohols and esters.*

**Specific Gravity** : *1.10 ± 0.10*

**Solids (by weight)** : *± 60%.*

**Colour** : *Clear*

**Spreading Rate** : *8-10 sq. meter / litre @ 40 microns DFT (Catalyzed)*

---

### **APPLICATION**

**Finishing** : *High gloss to matt.*

**Drying Time** : *Dry to tack free* 20 – 30 minutes @ 25°C  
*Dry for stacking* 8 hours @ 25°C

**Mixing Ratio** : *100 parts of AC Lacquer Topcoat*  
*10 parts of AC Hardener*  
*40 parts of AC Thinner*

**Pot Life** : *> 8 hours*

**Clean Up** : *AC Thinner*

---

### **STORAGE AND CAUTIONS**

**Shelf Life** : *1 year @ 25°C, provided that the product is stored under dry cool condition.*

**Cautions** : *Contents flammable.*  
*Keep away from heat, sparks and open flame.*  
*Avoid contact with skin and eyes.*  
*Avoid direct contact with vapour and spray mist.*  
*Use with adequate ventilation.*